


ATTACHMENTS
THAT BOOST PRODUCTIVITY
ALL YEAR ROUND

Whether you're working through the heat of summer or the dead of winter, our attachments are made to boost your earning potential the whole year through. So you can maximize your profits while getting the best results possible.



POWER LIFT



TRIPLE BAGGER/
DUMP HOPPER
WITH POWER
ASSIST (LZ only)
Weight kit required for
this attachment



12-VOLT
OUTLET KIT



LIGHT KIT



ULTRA TRACTION
TIRE/RIM



72" SNOW BLADE

ALSO AVAILABLE:

- MULCH KIT
- SEAT SUSPENSION KIT (L only)
- REAR STRIPING ROLLER (L only)

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

* As rated by Kohler, all power levels are rated at 3600 RPM per SAE J1940 gross.

**As rated by Kawasaki, horsepower tested in accordance with SAE J1995 and rated in accordance with SAE J2723 and certified by SAE International

† See your local Cub Cadet Independent Dealer for warranty details. Cub Cadet commercial products are intended for professional use.

773-05724 Printed in U.S.A. 12/14 © 2015 Cub Cadet



ENGINE	TANK LZ 54		TANK LZ 60
Engine Type	Commercial-grade Kawasaki® FX Series V-Twin OHV		
Engine Displacement/ Orientation	•———— 852cc/Vertical ———•		
Engine Horsepower	•———— 27 HP** ———•		
Engine Fuel	•———— Gasoline ———•		
Lubrication/Filter	•—— Full pressure w/ spin-on filter ——•		
Cooling System	•———— Air ———•		
Air Cleaner	•—— Heavy-duty canister air filter ——•		
Alternator	12V – 15 amp regulated		12V – 20 amp regulated
Fuel Capacity	•———— Twin 7.5 gal. (15 gal. total) ——•		
Fuel Gauge	•—— Standard (mounted on tank) ——•		
DRIVE SYSTEM			
Drive System	HTG PARKER™ Torqpact 14cc pumps and 280cc per-rev wheel motors		
Ground Speed	•—— Fwd: 12 mph/Rev: 6 mph ——•		
Hydraulic Fluid	•— Castrol Edge w/ Syntec Power 5W-50 —•		
Hydraulic Fluid Capacity	•———— 7 qt. total ———•		
Hydraulic Oil Filter	•—— Individual filter cartridges standard ——•		
Lap Bar Dampers	•———— Standard ———•		
Return to Neutral	•———— Standard ———•		
Braking/Parking Brake	•—— Dynamic drum, lever control ——•		
STEERING			
Caster Wheel/ Pivot Bearings	•—— Steel bushing, greasable ——•		
Front Axle	•— Fabricated w/ tapered roller bearings —•		
Controls	•— Quick-adjust lap bar system (toolless) —•		
CHASSIS			
Frame	Heavy-duty rail frame 3/8" x 5" laser cut steel w/ tie-down slots		
TIRES			
Front Tire Size	•—— 13" x 6.5" – 6" (smooth) ——•		
Rear Tire Size	24" x 12" – 12" (turf/smart traction tread/self clean)		
DIMENSIONS			
Length/Width/Height	86.5" / 49.5" / 73.5"		86.5" / 55.5" / 74"
Wheelbase	•———— 54" ———•		
Front Track Width	•———— 43" ———•		
Rear Track Width	•———— 53" ———•		
Weight (approx.)	1,100 lbs.		1,200 lbs.
MOWER DECK			
Deck Size/Type	54" sloped-nose		60" sloped-nose
Deck Style/System	•———— Floating ———•		
Deck Blades	•—— Triple-blade/High-lift blade standard ——•		
Deck Construction	10-gauge fabricated w/ 7- & 10-gauge reinforcements		
Deck Drive	•—— Belt – Kevlar® B-section ——•		
Deck Height Adjustment	•—— 1" – 5" (in .25" increments) ——•		
Blade Spindle Construction	•—— Cast-aluminum ——•		
Deck PTO	•—— Electronic fingertip engagement ——•		
Front Anti-Scalping Wheels/ Nose Roller	•—— 2 standard greasable/2-nose wheels ——•		
Rear Anti-Scalp Rollers/ Striper	•—— Full width, adjustable ——•		
ADDITIONAL SPECIFICATIONS			
ROPS	Standard, foldable/2-position lock (ISO 21299, OSHA 1928)		
Monitor/Hour Meter	•———— Standard ———•		
Seat Type	High-back, premium suspension w/ lumbar adjust angled back and Elasticity Vibration Control (EVC) comfort control seat w/ armrests		
Cup Holder	•———— Standard ———•		
Storage Box	•———— Standard ———•		
Rear Bumper & Hitch	Heavy-duty rear bumper w/ hitch standard		
WARRANTY†			
	3-yr limited commercial warranty† (no hour limitations)		

TANK™ L/LZ SERIES

COMMERCIAL ZERO-TURN RIDERS

DESIGNED FOR PROFESSIONAL DAILY USE ON FLAT TERRAIN. UP TO 15 ACRES.

FEATURES

48", 54" OR 60" FABRICATED
COMMERCIAL-GRADE DECK

COMMERCIAL-GRADE
KOHLER® COMMAND® PRO
OR KAWASAKI® FX
SERIES ENGINES

PREMIUM SEAT DESIGN
OPTIONS WITH ELASTICITY
VIBRATION CONTROL
SEATING SYSTEM WITH
ARMRESTS

TOOLLESS QUICK-ADJUST
LAP BAR SYSTEM
(LZ MODELS)

PIVOTING FRONT AXLE

3-YEAR LIMITED
COMMERCIAL WARRANTY†
WITH NO HOUR LIMITATION
(LZ MODELS)


†See specifications for warranty information.



ENGINEERED TO DELIVER PROFESSIONAL STRENGTH.

Maximum power and extra-tough construction lets you tackle acres of tough terrain, get the job done and get on to the next one. Unmatched ergonomics lets you do it all in amazing comfort. Incredible durability means you can enjoy it all for years to come.

INDUSTRY-LEADING FEATURES. THAT'S THE STRENGTH OF THE CUB CADET ADVANTAGE.



UNBEATABLE CORROSION PROTECTION AND DURABILITY

The Cub Cadet Triple Guard Corrosion Defense System™ with E-Coat delivers automotive-grade corrosion resistance against the elements and wear and tear, ensuring complete protection of critical components for years of reliable performance and a lasting professional appearance.

TOUGHNESS IS AT THE CORE

The laser-cut, full-length commercial-grade steel frame sets the standard for professional riders. Designed to absorb the stress of hours of operation in even the roughest terrain, you can count on it to last like no other. A limited lifetime warranty† backs that up.



POWER THAT PROS DEMAND

Ultra-high-performance, commercial-grade engines with heavy-duty remote canister air filtration deliver more power, more efficiency and more life for years of reliable service.



YOUR INDEPENDENT DEALER—EXPERT SERVICE. LOCALLY OWNED.
THE ADVICE, SELECTION AND SUPPORT YOU NEED TO FIND THE RIGHT FIT
IS AT YOUR LOCAL CUB CADET DEALER.

ENGINE	TANK L 48	TANK L 54
Engine Type	Commercial-grade Kohler® Command® PRO V-Twin OHV	Commercial-grade Kawasaki® FX Series V-Twin OHV
Engine Displacement/Orientation	694cc/Vertical	726cc/Vertical
Engine Horsepower	22.5 HP*	23.5 HP**
Engine Fuel	Gasoline	
Lubrication/Filter	Full pressure w/ spin-on filter	
Cooling System	Air	
Air Cleaner	Heavy-duty canister air filter	
Alternator	12V – 15 amp regulated	12V – 20 amp regulated
Fuel Capacity	7.5 gal.	
Fuel Gauge	N/A	

DRIVE SYSTEM	
Drive System	HTE PARKER™ Torqpack 10cc pumps and 260cc wheel motors
Ground Speed	Fwd: 10.5 mph/Rev: 6 mph
Hydraulic Fluid	Castrol Edge w/ Syntec Power 5W-50
Hydraulic Fluid Capacity	7 qt. total
Hydraulic Oil Filter	Individual filter cartridges standard
Controls	Adjustable lap bar system
Lap Bar Dampers	Standard
Return to Neutral	Standard
Braking/Parking Brake	Dynamic drum, lever control

STEERING	
Caster Wheel/Pivot Bearings	Ball bearing, greasable
Front Axle	Pivoting steel axle

CHASSIS	
Frame	Heavy-duty rail frame 3/8" x 5" laser cut steel w/ tie-down slots

TIRES	
Front Tire Size	13" x 6.5" – 6" (smooth)
Rear Tire Size	24" x 9.5" – 12" (turf/smart traction tread/self clean)

DIMENSIONS		
Length/Width/Height	86.5" / 49.5" / 73.5"	86.5" / 55.5" / 74"
Wheelbase	54"	
Front Track Width	43"	
Rear Track Width	50"	52"
Weight (approx.)	1,110 lbs.	1,150 lbs.

MOWER DECK		
Deck Size/Type	48" sloped-nose	54" sloped-nose
Deck Style/System	Floating	
Deck Blades	Triple-blade/High-lift blade standard	
Deck Construction	10-gauge fabricated w/ 7- & 10-gauge reinforcements	
Deck Drive	Belt – Kevlar® B-section	
Deck Lift	Single pedal, spring-assisted	
Deck Height Adjustment	1" – 5" (in .25" increments)	
Blade Spindle Construction	Cast-aluminum	
Deck PTO	Electronic fingertip engagement	
Front Anti-Scalping Wheels /Nose Roller	2 standard, greasable/2-nose gauge wheels	

ADDITIONAL SPECIFICATIONS		
ROPS	Standard, foldable/2-position lock (ISO 21299, OSHA 1928)	
Monitor/Hour Meter	Standard	
Seat Type	Elasticity Vibration Control (EVC) comfort seat w/ armrests	
Cup Holder	Standard	Standard
Storage Box	–	–
Rear Bumper & Hitch	Heavy-duty rear bumper w/ hitch standard	

WARRANTY†	
	2-yr limited commercial warranty† (no hour limitations) or 4-yr/800 hour limited residential warranty†

ENGINE	TANK L 60 KH	TANK L 60 KW
Engine Type	Commercial-grade Kohler Command PRO V-Twin OHV	Commercial-grade Kawasaki FX Series V-Twin OHV
Engine Displacement/Orientation	747cc/Vertical	852cc/Vertical
Engine Horsepower	23.5 HP*	27 HP**
Engine Fuel	Gasoline	
Lubrication/Filter	Full pressure w/ spin-on filter	
Cooling System	Air	
Air Cleaner	Heavy-duty canister air filter	
Alternator	12V – 20 amp regulated	12V – 15 amp regulated
Fuel Capacity	7.5 gal.	
Fuel Gauge	N/A	

DRIVE SYSTEM		
Drive System	HTE PARKER Torqpack 10cc pumps and 260cc wheel motors	HTE PARKER Torqpack 10cc pumps and 240cc wheel motors
Ground Speed	Fwd: 10.5 mph/Rev: 6 mph	
Hydraulic Fluid	Castrol Edge w/ Syntec Power 5W-50	
Hydraulic Fluid Capacity	7 qt. total	
Hydraulic Oil Filter	Individual filter cartridges standard	
Controls	Adjustable lap bar system	
Lap Bar Dampers	Standard	
Return to Neutral	Standard	
Braking/Parking Brake	Dynamic drum, lever control	

STEERING		
Caster Wheel/Pivot Bearings	Ball bearing, greasable	
Front Axle	Pivoting steel axle	

CHASSIS		
Frame	Heavy-duty rail frame 3/8" x 5" laser cut steel w/ tie-down slots	

TIRES		
Front Tire Size	13" x 6.5" – 6" (smooth)	
Rear Tire Size	24" x 9.5"– 12" (turf/smart traction tread/self clean)	

DIMENSIONS		
Length/Width/Height	86.5" / 55.5" / 74"	86.5" / 49.5" / 73.5"
Wheelbase	54"	
Front Track Width	43"	
Rear Track Width	52"	60"
Weight (approx.)	1,200 lbs.	

MOWER DECK		
Deck Size/Type	60" sloped-nose	
Deck Style/System	Floating	
Deck Blades	Triple-blade/High-lift blade standard	
Deck Construction	10-gauge fabricated w/ 7- & 10-gauge reinforcements	
Deck Drive	Belt – Kevlar B-section	
Deck Lift	Single pedal, spring-assisted	
Deck Height Adjustment	1" – 5" (in .25" increments)	
Blade Spindle Construction	Cast-aluminum	
Deck PTO	Electronic fingertip engagement	
Front Anti-Scalping Wheels /Nose Roller	2 standard, greasable/2-nose gauge wheels	

ADDITIONAL SPECIFICATIONS		
ROPS	Standard, foldable/2-position lock (ISO 21299, OSHA 1928)	
Monitor/Hour Meter	Standard	
Seat Type	Elasticity Vibration Control (EVC) comfort seat w/ armrests	Elasticity Vibration Control (EVC) suspension comfort seat w/ armrests
Cup Holder	Standard	
Storage Box	–	–
Rear Bumper & Hitch	Heavy-duty rear bumper w/ hitch standard	

WARRANTY†	
	2-yr limited commercial warranty† (no hour limitations) or 4-yr/800 hour limited residential warranty†